



NESTE 2-T MARINE

Two-stroke Outboard Engine Oil

NMMA TC-W 3 (BIA TC-W)

API TD

Neste 2-T Marine is a two-stroke engine lubrication oil. It is based on a SAE 40 paraffinic base oil with a 20% solvent fraction to ensure blending. New ash-free additives prevent wear and corrosion, and deposit formation on pistons, combustion chambers and exhaust ports. Neste 2-T Marine lubricates modern high speed outboard engines, eg. M efficiently.

TYPICAL CHARACTERISTICS

Densitykg/m ³ 15°C	872
Flash Point°C (COC)	58
Pour Point°C	-42
Viscosity Index	142
ViscositycSt/ 40 °C	8,5
Sulphated ash p-%	0,001

Neste 2-T Marine oil is particularly suitable for low-proportion mixtures used in high-power water-cooled outboard engines, and it meets the required NMMA TC-W 3 (previously BIA TC-W) quality standard. It can also be used in injection lubricated outboard engines, and it is particularly suitable for modern gasolines.

The oil is dyed green so that it is possible to see if the fuel blend contains oil. Neste 2-T Marine can also be used in other two-stroke engines. (Synthetic Neste 2-T Super and fully synthetic Neste 2-T Super Racing or biodegradable fully synthetic Neste 2-T Super Bio are recommended for demanding professional use in chain saws, snowmobiles and other air-cooled engines)

NMMA TC-W3 R-92001

Neste Markkinointi Oy

PL 95, 00095 NESTE OIL

www.neste.fi

Technical service

+358 200 11311

Updated 22.8.2012

Print

Close