



## NESTE 2-T SUPER

Synthetic 2-stroke engine oil

TSC-3

API TC

The base oil in Neste 2-T Super 2-stroke engine oil is a blend of fully synthetic polyalphaolefin and paraffinic mineral oil. Oil performance is intensified by low-ash additives developed particularly for 2-stroke engines to improve lubrication power, to reduce wear, deposit and carbon formation on piston rings, and to prevent corrosion. This oil contains 18% solvent, which ensures a good oil-fuel mixture at sub-zero temperatures. The base oil is SAE 50.

### TYPICAL CHARACTERISTICS

Densitykg/m <sup>3</sup> 15°C	858
Flash Point°C (COC)	110
Pour Point°C	-45
Viscosity Index	143
ViscositycSt/ 100 °C	7,5
Sulphated ash p-%	0,12

Neste 2-T Super is designed to lubricate fast-rotating high-power air and water-cooled two-stroke engines. It is suitable for blending and for injection lubrication systems. Special applications include motorbikes, mopeds, snowmobiles, chainsaws, lawnmowers, etc. The synthetic base oil component helps to guarantee extremely efficient lubrication, deposit-free combustion and low smoke formation tendency. The oil is dyed green to help users see whether the fuel blend contains oil. Use according to the engine manufacturer's instructions. Neste 2-T Marine is recommended for outboard engines, and Neste 2-T Super Racing for high power engines, f.ex. in snow mobiles and Aprilia motor bikes.

API TC

TSC-3

SAE 50 (oil component)

Neste Markkinointi Oy  
PL 95, 00095 NESTE OIL  
www.neste.fi

Technical service  
+358 200 11311  
Updated 5.5.2015

Print

Close