

FISKE BROTHERS REFINING COMPANY

NEWARK, NEW JERSEY 07105 . TOLEDO, OHIO 43605

FISKE'S 4050 CUTTING OIL

4050 Cutting Oil is a lard, sulfurized, mineral cutting oil possessing exceptional lubricating properties. It is highly recommended for automatic screw machines and turret lathes.

4050 Cutting Oil offers the advantages of greater production, lowered cost, prolonged tool life and better finish. It lubricates at the cutting edge protecting both the tool and the material and ensures a smooth finish on the work.

4050 Cutting Oil permits closer observation of the work which is a definite aid in production.

METALS: Stainless steels, tool steels, high speed steels, monel, etc. Not recommended for

copper, brass or bronze.

OPERATIONS: Automatic screw machines, turret lathes, threading, milling, boring, drilling,

reaming, etc.

TYPICAL CHARACTERISTICS:

Viscosity @ 100°F., SUS/cSt	285/61
Flash Point °F./°C.	350/177
Fire Point °F. /°C.	375/190
API Gravity	25.7
Sulfur	Yes
Active Sulfur	Yes
Chlorine	Yes
Fatty Material	Yes
Color	Dark Brown

4050 Cutting Oil is available in the following:

Packaging Available	<u>Part Number</u>
Ctn. 4/1 gallon jugs	F0586-056
5 gallon pail	F0586-060
55 gallon drum	F0586-062