

PRODUCT DATA SHEET



6 IN 1® BIODEGRADABLE MULTIPURPOSE LUBRICANT

6 IN 1 Biodegradable Multipurpose Lubricant, commonly known as Bio-Bel 6 In 1 Lubricant, is a biodegradable, multipurpose lubricant formulated using a readily renewable bio-base.
6 IN 1 Biodegradable Multipurpose Lubricant is a high performance penetrating lubricant that cleans, protects and offers effective water displacement. 6 IN 1 Biodegradable Multipurpose Lubricant is readily biodegradable and safe for environmentally sensitive areas such as marinas, boats and landscaping equipment, chain saws and on hunting and fishing equipment. Although 6 IN 1 Biodegradable Multipurpose Lubricant is the product of choice for environmentally sensitive areas, it is a true high performance lubricant and can be used for a complete range of industrial and household applications.

Applications

- ♦ Industrial bearings, chains, conveyors, instruments, hand tools, parts disassembly
- ♦ Sports equipment firearms, fishing reels, downriggers
- ♦ Automotive/Motorized cables, hinges, locks, levers, threads, battery terminals
- ♦ Marine equipment linkages, cables, hinges, locks
- ♦ Consumer door hinges, locks, zippers, saw blades, metal drawers, cameras

Features and Benefits

✦ High film strength
 ✦ Penetrant and Rust Buster
 ✦ Cleaner
 ✦ Protectant
 ✦ Protectant
 ✦ Eliminates moisture
 芹 Reduces friction and wear.
 Ł Loosens frozen parts.
 Removes rust and grime.
 Inhibits corrosion.
 Displaces water.

General Description

6 IN 1 Biodegradable Multipurpose Lubricant is a high performance biodegradable, multi-purpose fluid lubricant. **6 In 1 Biodegradable Multipurpose Lubricant** that contains special additives which provide high film strength to resist metal-to-metal contact and reduce wear. **6 IN 1 Biodegradable Multipurpose Lubricant** offers protection against corrosion and rust, as it displaces water and penetrates. It cleans as it lubricates.

Product No. 12350, 12351

Page 1 of 2 1/20/2015

With continual research and development, Bel-Ray Company reserves the right to change the information contained herein. The Company is not responsible for misuse or misapplication of its products.

6 IN 1® BIODEGRADABLE MULTIPURPOSE LUBRICANT

TYPICAL PROPERTIES

Product No.	<u>12350</u>	<u>12351</u>
	Bulk	Aerosol
Propellant		CO_2
Viscosity, ASTM D445 @ 40°C, cSt	7.31	7.31
Pour Point, ASTM D97 °C (°F)	-15 (5)	-15 (5)
Rust Test, ASTM D665, Procedure A & B	Pass	Pass
Falex EP Test, ASTM D3233 Method B Non-seizure Load, lbf	2000	2000
Flash Point, ASTM D93 °C (°F)	115 (239)	115 (239)
Color	Amber	Amber

Page 2 of 2 1/20/2015