



## Aircol SR Range

Synthetic rotary compressor lubricant

### Description

The Castrol Aircol™ SR compressor oil range of premium lubricants are designed for use in rotary screw compressors and are based on polyalphaolefin (PAO) fluids.

### Application

Aircol SR is suitable for use in oil flooded rotary screw compressors usually met in marine applications. Aircol SR range is fully compatible with nitrile, silicone, polyurethane and fluropolymer seal materials typically used in compressor units. It is not compatible with butadiene styrene (SBR) or ethylene propylene (EPDM) seals.

Aircol SR is classified as follows:

- DIN 51506 classification - VDL
- ISO 6743/3 - DAG, DAH and DAJ for rotary air compressors

Aircol SR grades meet the requirements of:

- Atlas Copco 8000 hour oil drain interval
- Kaeser

### Advantages

- Increased oil service life
- Very low deposit forming tendency, extends service life of filters and separators.
- Outstanding oxidation stability and antiwear performance providing long lubricant and equipment life.
- Ester-free formulation eliminates the formation of corrosive acids leading to longer equipment life.
- Excellent water separation characteristics allow condensation to readily separate from the oil, minimising the risk of emulsions which could block the oil separator element.

## Typical Characteristics

Name	Method	Units	Aircol SR 32	Aircol SR 46
Density at 15°C	ISO 12185, ASTM D4052	g/ml	0.83	0.84
Kinematic Viscosity at 40°C	ISO 3104, ASTM D445	mm <sup>2</sup> /s	32	46
Kinematic Viscosity at 100°C	ISO 3104, ASTM D445	mm <sup>2</sup> /s	6.1	7.8
Viscosity Index	ISO 2909, ASTM D2270	-	137	137
Foam Sequence I	ISO 6247, ASTM D892	mls/mls	10/0	10/0
Pour Point	ISO 3016, ASTM D97	°C	-54	-54
Flash Point, COC	ISO 2592, ASTM D92	°C	264	264
Rust Test (24hrs, Synthetic Sea Water)	ISO 7210, ASTM D665B	-	Pass	Pass
RPVOT	ASTM D2272	Mins	4,500	3,000
FZG Fail Stage (A8.3/90)	ISO 14635-1, DIN 51354	-	8	9

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings.

Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Aircol SR Range

30 Mar 2012

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Marine, Technology Centre, Whitchurch Hill, Pangbourne, Reading RG8 7QR, United Kingdom

[www.castrolmarine.com](http://www.castrolmarine.com)