

## Product Information

# AQUA MAX 2

## OUTBOARD TWO STROKE OIL

---

### Description

Aqua Max 2 is approved by the NMMA to TC-W3™ and has been developed to meet the need for a specialised ash free outboard motor oil for today's high powered multi-cylinder two cycle engines. The ashless formulation provides an excellent lubricating film that leads to improved engine performance and reduced wear for engine components even if temporary overheating occurs. Aqua Max 2 provides: -

- Maximum film strength
- Freedom from ring sticking
- No plug fouling or pre-ignition
- Anti-wear, anti-scuffing protection
- Reduced smoke and clean burning characteristics
- Reduced deposit formation in ports

### Applications

Recommended for use in two cycle water cooled outboard engines using premix or oil injection, from high powered down to small cylinder auxiliary engines.

Also suitable for certain two cycle air-cooled engines operating under normal duty.

### Performance Levels

Aqua Max 2 meets the requirements of all major engine manufacturers and is certified by the National Marine Manufacturers Association (NMMA) to specification TC-W 3™ R-94102B.

Meets the requirements of JASO FB.

### Physical Characteristics

Colour	Blue / Purple
Kinematic Viscosity at 100 °C, cSt.	7.3
Kinematic Viscosity at 40 °C, cSt.	46
Sulphated Ash, %Wt.	<0.001
Pour Point, °C	-30
Flash Point (Closed) °C	85
TBN, mg/KOH/g	4.5



Certificate No. FM 21756  
BS EN ISO9001 2000

Morris Lubricants, Castle Foregate, Shrewsbury, Shropshire SY1 2EL

Telephone (01743) 232200 Fax (01743) 353584



Certificate No. EMS 60044  
BS EN ISO14001 1996