

AQUAWAY

2-stroke outboard engine oil

Product description

AQUAWAY is a 2-stroke engine oil for water cooled outboard engines. The product ensures good lubrication and prevents the forming of deposits at low operating temperatures.

Application areas

AQUAWAY is recommended for water cooled marine 2-stroke engines. Ash less technology ensures good lubrication and prevents the forming of deposits at low operating temperatures. The product is suitable as a premix in gasoline or in separate lubricating systems. AQUAWAY should be mixed in a 2 vol% ratio or in accordance with the engine manufacturer's specifications. The product is not suitable for land based 2-stroke engines.

Characteristics and advantages

The excellent protection against wear and corrosion prolongs the lifetime, provides good lubricity to the engine parts and keeps the engine free of deposits and combustion residues, even at low operating temperatures. The high fluidity and miscibility provides a reliable operation as a premix or in separate lubrication systems. AQUAWAY contains special corrosion inhibitors in order to avoid rust in saltwater.

Tests and approvals

Specifications: NMMA TC-W3

Handling and storage

Avoid skin contact. In the event of contact with skin, wash with soap and water. Dispose of used oil at a recycling station or equivalent. Safety data sheets are available for professional users and are supplied on request.

Typical Data

Characteristics	Typical value	Unit	Method
Density at 15°C	874	kg/m ³	ISO 12185
Pour point	-33	°C	ISO 3016
TBN	5.1	mg KOH/g	ASTM D 2896
Viscosity at 40°C	51.3	mm ² / s	ISO 3104
Viscosity at 100°C	8.6	mm ² / s	ISO 3104
Viscosity index	146	-	ISO 2909

Revision date 25-Jul-2014