



## ATF DEXRON IID

REV.1 OF MARCH /2013

### LEVELS OF QUALITY

*The lubricant **ATF DEXTRON IID** complies with the following international specifications:*

GM DEXRON IID · ZF TE-ML 02F, 03D, 04D, 09A, 11A-B, 14A, 17C · VOITH 55.6335.32 (G607) · MAN 339D · ALLISON C4 · CAT TO-2 · MB 236.1-236.7 · FORD MERCON M2C 138CJ

### PRODUCT DESCRIPTION

*DUGLAS OIL ATF DEXRON IID is a lubricant recommended for automatic transmissions, power steering, hydraulically assisted steering and torque convertors, whenever it is required a DEXRON II D product.*

*It is also used as an hydraulic oil covering a large temperature range for applications in the automotive, industry and marine field.*

### APPLICATIONS

It ensures excellent performances in terms of:

- frictional properties;
- thermal-oxidative stability;
- wear and corrosion resistance.

Thanks to the above mentioned features it also ensures both a low pour point and a reduced foaming tendency.

### TYPICAL FEATURES\*

Density at 15°C.Kg./dm3	ASTM D1298	0.860
Colour		Red
Viscosity at 100°C.cSt	ASTM D445	7.5
Viscosity Index	ASTM D2270	140
Flammability V.A.°C	ASTM D92	195
Pour Point °C	ASTM D97	-27

\*The above mentioned values are indicative of production average values and are not an integral part of the specification.

RA.M.OIL S.p.A.

Stabilimento: Via Filichito, 28 - 80013 Casalnuovo (NA) - tel +39 081.51.95.111

Uffici: Via Enrico Mattei, 37 - 80013 Casalnuovo (NA) - tel +39 081.31.70.911

P.IVA 00291350635 - Capitale Sociale € 12.000.000,00 int. vers.

info@ramoil.it - www.ramoil.it

