



## *Sasol ATF DX II*

### *AUTOMATIC TRANSMISSION FLUID*

#### *Description*

Sasol ATF DX II is a mineral oil automatic transmission fluid, formulated for excellent foam and oxidation-resistant, having frictional characteristics suitable for automatic transmissions employing high lock-up pressures.

Sasol ATF DX II is dyed red for easy identification.

#### *Application*

Sasol ATF DX II is recommended for most automatic transmission units and power steering units. It can also be used in applications requiring Allison C3 & C4 fluids, in off highway applications as well as certain ZF automatic transmissions.

#### *Features and Benefits*

Sasol ATF DX II is intended for:

- automotive automatic transmissions
- power steering systems
- gearboxes
- hydraulic systems
- certain rotary type air compressors

#### *Product Specifications*

Mercedes-Benz 236.1  
Allison C-4  
Denison HF-0  
Voith G607  
ZF TE-ML-14A  
MAN 339 type D

#### *Typical Characteristics*

<u>Property</u>	<u>Units</u>	<u>Typical</u>	<u>ASTM</u>
Density @ 20°C	kg/l	<b>0.867</b>	ASTM 4052
Viscosity			
@ 100°C	cSt	<b>7</b>	ASTM D445
@ 40°C	cSt	<b>37</b>	ASTM D445
@ -40°C	cP	<b>22 000</b>	ASTM D2983
Viscosity Index	°C	<b>175</b>	
Pour Point	°C	<b>-39</b>	ASTM D97
Flash Point (COC)	% mass	<b>215</b>	ASTM D92



### *Storage and Handling*

Use PVC, nitrile or other oil resistant gloves and protective clothing to prevent skin contact. Where eye contact is a potential hazard, goggles should be worn.

Avoid temperatures above 60°C and strong oxidizing agents.

Ambient temperatures and atmospheric pressures normally encountered within buildings or roofed-over outdoor storage areas are acceptable. Avoid entering areas where mists or vapours have built up as a result of abnormal temperatures or pressures without the proper breathing equipment and protective clothing.

### *Pack Information*

<u>Product Code</u>	<u>Pack Size</u>
	1x500ml
	20x500ml
	1x5L
	4x5L
	20L
	210 L