

Granville ATF MV

1 Litre & 5 Litre



Product Description

Granville ATF-MV is a fully synthetic automatic transmission fluid manufactured by selecting the latest quality additives and base oils to formulate a truly outstanding product. ATF-MV meets and exceeds a wide range of specifications and approvals making this product suitable for multi-vehicle applications.



* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	0004	5020618000044
5 Litre	0005	5020618000051

Quality Lubricants

Quality Lubricants

Quality Lubricants





Granville ATF MV

1 Litre & 5 Litre



Recommended for use by Granville for the following manufacturer's specifications

ATF SPII
ATF SPIII
ATF Type A, Suffix A (TASA)
Allison C4
Esso LT71141ATF
Ford Mercon
Ford Mercon SP
Ford Mercon V
Ford WSS-M2C 166-H
Ford WSS-M2C195-A
Ford WSS-M2C202-B
Ford WSS-M2C924-C
GM 93160393
GM 9986195
GM Dexron II D/E
GM Dexron III H/M
Honda ATF-Z1
Idemitsu K17
MB 236.3
MB 236.5
MB 236.6
MB 236.7
MB 236.9
Mopar ATF+3
Mopar ATF+4 (7176)
Nissan Matic J
Nissan Matic K
Saab 3309
Saab 93 165 147
Shell LA2634
TES-295
Texaco 7045-E
Texaco ETL-8072B
Texaco N402
Toyota JWS3309
Toyota T-IV
Toyota WS
VAG G 052 990 -A2
VAG G-055-025-A2
VAG G052 162
Voith G607
Volvo 1161540-8
ZF TE-ML-03D
ZF TE-ML-04D
ZF TE-ML-14B
ZF TE-ML-16L
ZF TE-ML-17C

Quality Lubricants

Quality Lubricants

Quality Lubricants





Granville ATF MV

1 Litre & 5 Litre



Product Benefits

- * Fully synthetic
- * Outstanding wear protection
- * Multi-vehicle applications

Product Usage

Granville ATF-MV is designed for use in automatic transmissions where recommended also as a power steering fluid where recommended. For automatic transmissions where this specification lubricant is required.

Directions for Use

As recommended by the vehicle manufacturer.

Storage Instructions

Store sealed in a cool, dry place.

Shelf Life

5 years from date of manufacture.

Appearance	: Red liquid
Odour	: Characteristic
Specific Gravity	: 0.85 @ 15.6°C (typical)
Solubility	: Insoluble in water
Flashpoint	: >200°C
Kinematic Viscosity @ 100°C	: 9.96 cSt (typical)

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

** The information contained in this leaflet is provided to enable the user to assess the product and should not be taken as a specification. All information provided is given in good faith, we can however not assume liability. It is up to the user to ensure that the information and the product is suitable for the use intended.*

