

CHAIN SAW OIL

Chainsaw oil

Product description

CHAIN SAW OIL is a mineral oil based chain saw oil with very good adhesion, film strength, creeping ability and protection against wear.

Application areas

CHAIN SAW OIL is recommended for year-round use for felling and cutting saws in forest machines and for regular chainsaws. The oil is miscible with other mineral oil or rapeseed oil based chain saw oils.

Characteristics and advantages

CHAIN SAW OIL has very good adhesion, film strength and creeping ability. The product penetrates easily into places where lubrication is required. CHAIN SAW OIL is formulated to reduce wear, which increases the life of both chains and bars. The oils viscosity, adhesion and good low temperature properties make it suitable for year-round use. The colour and viscosity of the product may vary.

Tests and approvals

Demonstrates very good performance in operation

Handling and storage

Avoid skin contact. Clean with soap and water in the event of contact with the skin. Dispose of used oil at a recycling station or equivalent. Safety data sheets are available on www.statoillubricants.com or supplied on request.

Typical Data

Characteristics	Typical value	Unit	Method
Density at 15°C	882	kg/m ³	ISO 12185
Flash point COC	130	°C	ISO 2592
Pour point	-27	°C	ISO 3016
Viscosity at 40°C	90	mm ² /s	ISO 3104

Revision date 16-Jan-2015