

Q8 Chainsaw Oil

Lubricant for Power-saw Chains

Product Description

Q8 Chainsaw Oil has been specially formulated from high quality base oils incorporating an adhesive agent to enable it to resist "fling-off" in use.

Applications

Q8 Chainsaw Oil is recommended for the lubrication of chains of all types of power chain-saws. Its built-in adhesiveness enables it to remain in situation despite the hostile operating environment of a chain-saw; in which vibration, excessive G-forces and physical removal by saw dust and adjacent surfaces are factors which combine to remove all but the most tenacious lubricants. Sprocket surfaces, link pins and rollers are thus adequately lubricated, protecting the chain from premature failure and significantly extending its useful working life.

Main Features and Benefits

- Tenacious, adhesive film resists "fling-off" and wiping effect of the saw-cutting action
- Lubricates and protects all parts of the chain linkage and drive
- Helps to prevent premature chain failure and to extend working life
- Reduces the effects of hostile working conditions

Typical Inspection Data

Property	Method	Unit	Typical value
Absolute Density, 15°C	D 4052	kg/m ³	886
Kinematic Viscosity, 40°C	D 445	mm ² /s	150
Flash point	D 93	°C	240
Texture	KPI5		Stringy

Health and Safety

Reference should be made to the relevant Q8 Material Safety Data Sheet before use.

Oct 05



Kuwait Petroleum International Lubricants (UK) Ltd

Knowsthorpe Gate, Leeds LS9 0NP. UK

For further assistance contact the Technical help line Telephone +44 (0) 113 2365 223, Fax +44 (0) 870 238 4673

For Customer Sales Contact, Tel +44 (0) 113 2365 204, Fax +44 (0) 113 2485 026. www.Q8Oils.co.uk

In line with our policy of continued improvement, Kuwait Petroleum International Lubricants reserve the right to change specification and availability without prior notice



technical data