

# CHAINWAY 220

## Chainsaw oil

### Product description

CHAINWAY 220 is an extreme pressure or EP oil, specifically developed for central lubrication of the saw chain, cutting bar and drive gear in sawing machines. The product contains additives which provide a high level of protection against wear and corrosion.

### Application areas

CHAINWAY 220 is specifically designed to give good functionality in lubrication of chain, sword and gear sprockets for sawing machines. The product can be used all year round under hard conditions and varying temperatures. Follow manufacturer's instructions for tightening the chain carefully - never tighten the chain, while it is hot.

### Characteristics and advantages

CHAINWAY 220 has excellent adhesion and the viscosity SAE 50. This ensures that the oil sticks to the chain at high temperatures. CHAINWAY 220 protects chain, cut and sword against corrosion, both during operation as well as during storage, and prevent "caking" of sawdust and oil on the sword blade. EP additives protects all joints and moving parts against wear at high loads and high temperatures.

### Tests and approvals

CHAINWAY 220 shows very good performance in operation

### Handling and storage

For additional information, see Safety Data Sheet

### Typical Data

Characteristics	Typical value	Unit	Method
Density at 15°C	889	kg/m <sup>3</sup>	ISO 12185
Flash point COC	246	°C	ISO 2592
Pour point	-9	°C	ISO 3016
Viscosity at 40°C	209	mm <sup>2</sup> /s	ISO 3104
Viscosity at 100°C	19.6	mm <sup>2</sup> /s	ISO 3104
Viscosity index	109	-	ISO 2909

Revision date 10-Feb-2015