

CEPSA CICONIA 30

Description



CEPSA CICONIA 30 oil has been developed for the lubrication of crankcases in low-speed two-stroke diesel marine engines.

The product is manufactured with highly-refined oil bases and delivers excellent anti-rust and anti-foam properties. One of its core features is its low alkalinity, which enables the neutralization of acidic fuel products that may enter the engine's crankcase cavity. Features high detergent properties and excellent rust stabilization, ensuring clean engines.

Product performance

- Excellent anti-wear properties.
- Excellent detergent/dispersant properties ensuring the crankcase remains clean
- Protects all the engine's components from rust.
- Prevents the build up of foam.
- Features ideal cleaning properties for oil filters.

Specifications

- MAN B&W Diesel
- WÄRTSILA

Typical Characteristics

PROPERTIES	ASTM REGULATION	CEPSA CICONIA 30
SAE GRADE	---	30
Density 15 °C, kg/l	D-4052	0.894
Flash point V/A, °C	D-92	>220
Freezing point, °C	D-97	-6
Cst viscosity at 40 °C	D-445	110
Cst viscosity at 100 °C	D-445	11.95
Viscosity index	D-2270	96
Total Base Number, mg KOH/g (min)	D-2896	5

Health & Safety and Environment

In compliance with current legislation there is a Safety Data Sheet available featuring product hazard information, safety instructions, first aid measures and environmental information.