



## NESTE CITY PRO W LONGLIFE III 5W-30

Volkswagen 504.00/ 507.00 engine oil for extended oil drain intervals.

SAE 5W-30

VW 504.00 and 507.00

ACEA C3

Mercedes-Benz Approval 229.51

BMW Longlife-04

Neste City Pro W LongLife III 5W-30 is especially developed for the LongLife Service used in VW, Audi, Skoda and Seat diesel and gasoline engines with extended oil drain intervals.

It is suitable for engines with DPF (Diesel Particulate Filter) emission aftertreatment system which requires low/mid SAPS (Sulphated Ash, Phosphorus and Sulphur) oil. In these diesel engines engine oil requirement is VW 507.00. In gasoline engines requirement is VW 504.00.

Neste City Pro W LongLife III is suitable for most VAG group LongLife Service cars excluding V10 and R5 TDi PD diesel engines which require VW 506.01 type of engine oil. Older than -98 year models diesel engines with pump injector technology and normal 15 000 km oil drain intervals also Neste City Standard 5W-40 (VW 505.01) engine oil can be used.

Extended oil drain intervals may be applied as indicated by the car manufacturer.

When using extended oil drain intervals use Neste City Pro W LongLife III 5W-30 as a top up oil.

### TYPICAL CHARACTERISTICS

### 5W-30

Densitykg/m <sup>3</sup> 15°C	853
Flash Point°C (COC)	230
Pour Point°C	-42
Viscosity Index	170
ViscositycSt/ 40 °C	69
ViscositycSt/ 100 °C	11,8
Viscosity cP/ -30 °C	5800

Neste Markkinointi Oy  
PL 95, 00095 NESTE OIL  
www.neste.fi

Technical service  
+358 200 11311  
Updated 16.12.2013

[Print](#)[Close](#)