



NESTE CITY PRO 0W-20

Fully Synthetic Low Viscosity Motor Oil

API SN, SM

ACEA A1

ILSAC GF-5

Ford WSS-M2C930-A

Chrysler MS-6395

Fully synthetic high performance motor oil with low friction and low viscosity helps fuel saving.

It is developed especially for the Asian passenger cars like Toyota Lexus and Honda where a low viscosity SAE 0W-20 or 5W-20 oil is recommended. Suitable especially for hybrid cars where fuel economy and CO2 reduction is important.

With fully-synthetic Neste City Pro 0W-20 oil lubrication starts right away during cold start. Modern additive technology gives this low viscosity oil excellent protection against wear in high temperatures.

Ensure compatibility for your car from owner's manual or handbook if in doubt.

Use ILSAC GF-5 where GF-4 or GF-3 or GF-2 or GF-1 is recommended.

TYPICAL CHARACTERISTICS	0W-20
Densitykg/m ³ 15°C	844
Flash Point°C (COC)	220
Pour Point°C	-45
Viscosity Index	170
ViscositycSt/ 40 °C	46
ViscositycSt/ 100 °C	8,7
ViscositycP/ °C	5400

Neste Markkinointi Oy

PL 95, 00095 NESTE OIL

www.neste.fi

Technical service

+358 200 11311

Updated 26.2.2013

Print

Close