



## CMC 404 H

Two Stroke Crankcase System Oil Additive

### Description

CMC 404H is an additive concentrate that, when mixed with the appropriate amount of diluting oil, may be used for the lubrication of low speed marine crosshead engine crankcase systems.

### Technical Data

| Name                         | Method     | Units              | CMC 404H |
|------------------------------|------------|--------------------|----------|
| Viscosity, Kinematic @ 100°C | ASTM D445  | mm <sup>2</sup> /s | 25       |
| Viscosity, Kinematic @ 40°C  | ASTM D445  | mm <sup>2</sup> /s | 450      |
| Total Base Number, TBN       | ASTM D2896 | mg KOH/g           | 167      |
| Density @ 15°C, Relative     | ASTM D4052 | g/ml               | 1.060    |
| Flash Point, PMCC            | ASTM D93   | °C                 | 160      |

### Care and Handling

Avoid prolonged or repeated contact with skin. Wash thoroughly after handling.

### Packaging and Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

CMC 404 H  
07 May 2013  
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Marine, Technology Centre, Whitchurch Hill, Pangbourne, Reading RG8 7QR, United Kingdom

[www.castrolmarine.com](http://www.castrolmarine.com)