



CITGO COMPRESSOR OIL 35LP

Date 08/11

- DESCRIPTION:** CITGO Compressor Oil 35LP is a high-quality non-foaming, non-detergent compressor cylinder lubricant engineered for the requirements of air and gas compressors and older gas engines that utilize activated clay filtration.
- CITGO Compressor Oil 35LP employs high VI paraffinic base stocks with additives to inhibit oxidation, rust and corrosion, and possesses additional demulsibility characteristics.
- QUALITIES:**
- High viscosity index provides superior viscosity-temperature characteristics.
 - Low pour point for cold climate operations.
 - Low carbon forming tendencies together with oxidation resistance minimizes exhaust valve deposits.
- APPLICATIONS:** CITGO Compressor Oil 35LP is recommended for cylinder lubrication of reciprocating air and gas compressors.

TYPICAL PROPERTIES:**CITGO COMPRESSOR OIL 35LP**

Material Code	633746001
Gravity, ASTM D 4052, °API	29.2
Density, lb/gal	7.284
Flash Point, ASTM D 92, °F (°C)	554 (290)
Viscosity, ASTM D 445, cSt at 40°C	115
cSt at 100°C	12.3
Viscosity Index, ASTM D 2270	97
Pour Point, ASTM D 97, °F (°C)	-17 (-27)
Color, ASTM D 1500	L2.0
Total Acid No. mgKOH/g, ASTM D 664	0.1
Foam Test, Seq. I, ml, ASTM D 892	0-0
Seq. II, ml, ASTM D 892	0-0
Seq. III, ml, ASTM D 892	0-0
RPVOT, Oxidation, ASTM D 2272, minutes	320