



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105

Phone: 973-589-9150

Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605

Phone: 419-691-2491

Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

LUBRIPLATE CP-8A GEAR OIL

LUBRIPLATE CP-8A Gear Oil is formulated to be in accordance with AGMA Specification 8A Comp. Gear Oil.

LUBRIPLATE CP-8A Gear Oil is a non-EP oil, but is manufactured with 3 to 10% acidless tallow as required to meet AGMA Specifications.

LUBRIPLATE CP-8A Gear Oil will not mix with or dissolve in water. This product is recommended for use in cone drives and double-enveloping worm gear drives where such an oil is required.

Typical tests for LUBRIPLATE CP-8A Gear Oil are as follows:

<u>Typical Tests</u>	<u>CP-8A</u>
Viscosity SUS @ 100°F	4950
cSt @ 40°C	950
Viscosity SUS @ 210°F	230
cSt @ 100°C	47
Viscosity Index, Min.	95
Flash Point (COC), °F/°C	550/288
Fire Point (COC), °F/°C	600/316
Pour Point, °F/°C	+35/+2
AGMA No.	8A Comp.
ISO Viscosity Grade	1000

Packaging Available

35 lb. Pail
120 lb. Drum
415 lb. Drum

Part Numbers

L0141-035
L0141-039
L0141-040