



Cresta SHS

Steam cylinder oil

Description

Cresta™ SHS is formulated from selected base cylinder stocks to achieve the desirable characteristics of high flash point and oxidation stability. It possess good demulsibility, which means for the lubrication of the cylinders of high speed, totally enclosed steam engines, it does not materially reduce the demulsibility of the crankcase oil.

Application

Cresta SHS is designed for lubrication of steam engine cylinders and valves. It is also suitable for other purposes, such as the lubrication of heavily loaded slow-moving bearings and gears. It is also suitable for condensing engines using high pressure steam up to 200psi and superheat upto 345°C/653°F.

Typical Characteristics

Name	Method	Units	Cresta SHS
Appearance	Visual	-	Dark Brown Fluid
Relative Density @ 20°C/68°F	ISO 12185/ ASTM D4052	g/cm ³	0.92
Kinematic Viscosity at 40°C/104°F	ISO 3104/ ASTM D445	cSt	1000
Kinematic Viscosity at 100°C/212°F	ISO 3104/ ASTM D445	cSt	44
Viscosity Index	-	-	80
Flash Point, PMCC	ISO 2719/ ASTM D93	°C/°F	260/500

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

Cresta SHS

15 Nov 2011

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Marine, Technology Centre, Whitchurch Hill, Pangbourne, Reading RG8 7QR, United Kingdom

www.castrolmarine.com

