



Aral Degol CL 220 T

Gear oil type CL

Applications:

Aral Degol CL 220 T is a CL type gear oil, that fulfills the requirements of DIN 51517-2 with an expanded performance profile, according to the steel industry standard SEB 181 225. This product fulfills the requirements of the Morgoil-Bearing-Lubricant-Specification of the Schloemann-Siemag company. Special properties offer an excellent corrosion protection, good demulsibility, minimal foaming tendency characteristics and a high ageing protection ability.

Operational area:

Aral Degol CL 220 T can be used as a gear oil, circulation oil, hydraulic oil type HL, general machine lubricant or as compressor oil type VBL/VCL.

Technical Data

Density at 15 °C	g/ml	DIN 51757	0,888
Viscosity Index		DIN ISO 2909	93
Viscosity			
40 °C	mm ² /s	DIN 51562	219
100 °C	mm ² /s	DIN 51562	18,5
Flash point COC	°C	DIN ISO 2592	290
Pourpoint	°C	DIN ISO 3016	-15
Neutralization number	mg KOH/g	DIN 51558-1	0,1
Oxide ash	Gew. %	DIN EN ISO 6245	<0,01
Demulsion character. at 82 °C	min	DIN 51599	15
Foaming characteristics at 24 ml °C		ISO 6247	0

Remarks:

All data is subject to development for the product and the production process.

Version-No.: IS0012