
DELKOL ATF UNIVERSAL SYNTHETIC

Automatic Transmission Fluid

Product Description

DELKOL ATF UNIVERSAL SYNTHETIC is an exceptionally high performance lubricant that meets original equipment manufacturers' specifications for use in certain slip-controlled lock-up automatic transmissions.

Features and Benefits

The unique formulation of DELKOL ATF UNIVERSAL SYNTHETIC is designed to provide excellent lubrication of transmissions in specified Aisin-Warner slip-controlled lock-up automatic transmissions. These outstanding performance capabilities translate into significant operational benefits, including:

- Excellent lubricating characteristics for quiet operation and smooth shifting in approved transmissions
- Controlled friction properties for smooth and efficient transmission of power across all normal temperature ranges
- Helps to control transmission shudder and provide excellent vehicle driveability
- Helps to extend transmission life based on excellent wear control
- Long fluid life based on excellent oxidation resistance
- Excellent viscosity stability (high viscosity index) to help assure adequate lubrication without excessive thinning in severe high-temperature service or thickening at low starting temperatures
- Resistance to foaming
- Superb protection against rusting and corrosion
- Compatibility with synthetic rubber seal materials

Applications

DELKOL ATF UNIVERSAL SYNTHETIC is recommended for use in transmissions made by Aisin-Warner requiring fluids approved against JWS 3309 or GM 9986195. It is also recommended for service fill applications where Toyota T-IV, T4, T-III or T3 are called for. Please refer to the owners' manual for proper fluid requirements.

Delek Lubricants

P.O.B 31 Lod 71100 ISRAEL. Tel: 972-8-9270820, Fax: 972-8-8247072
www.deklelubes.com

SPECIFICATIONS

TOYOTA T/T-II/T-III/T-IV/D-2/WS	NISSAN MATIC FLUID C/D/J/K	Texaco 704E/N402 Texaco ETL 8072B
ALLISON C-4/TES 228	GM DEXRON IID/E &TASA/IIIG/IIIH	Mercedes 236.10
Suzuki ATF Oil Special	Mitsubishi/Hyundai/Kia SP-II/SP-III	Voith commercial ATs (55.6335)
Subaru ATF/PN K0710Y0700	Isuzu BESCO ATF-II/ATF-III	Daihatsu Alumix ATF Multi
MAZDA ATF M-3/M-V	JASO M315 Type 1A	Honda ATF Z1 (except cvt)
FORD M2C – 166H/Mercon FORD M2C – 202B/Mercon V FORD M2C – 919 E	ZF commercial ATs (TE-ML-14A/B) (ZF-TE-ML-03D/04D/09B/14A/14B/16L/17C)	MAN commercial ATs (MAN 339 Type Z-1/Z-2/Z-3/V-1/V-2)
Chrysler Mopar ATF +3/+4	Aisin Warner JWS 3309 ATs ub Euro Vehicles (including Volvo, Opel, VW, Renault & Porsche)	Volvo 1161540-8
GM Daewoo/GM US 88900925 (T-IV)	4/5 Speed European (BMW/MB/VW)	VW G055 025 Audi G052 025A2

Typical Properties

	DELKOL ATF UNIVERSAL SYNTHETIC
Viscosity	
cSt @ 100°C	7.5
cSt @ 40°C	36
cP @ -40°C (-40°F)	14,000
Viscosity Index	170
Flash Point, °C	220
Pour Point, °C	< -45
Density	0.848
Color	BROWN

Delek Lubricants

P.O.B 31 Lod 71100 ISRAEL. Tel: 972-8-9270820, Fax: 972-8-8247072
 www.deklelubes.com