



Delkol SJ

General Description :

Advanced engine oils series for gasoline engines fitted with fuel injection and catalytic converters, and for diesel engines in light vehicles.

Viscosity 15W40 is particularly suitable for a mixed fleet of gasoline engines and light vehicle diesel engines from 1996 on.

Ultra 40 SJ is also suitable for old cars.

Specifications :

Delkol SJ 15W40 :

API SJ/CF-4

VW 501/505

MAN 271

VOLVO VDS

ALLISON C-4

MB 227.5/228.1

ACEA A2-96, B2-96, E2-96

Delkol SJ 20W50:

VW 501/505

ACEA A2, B2

API SJ

MB 228.1

Delkol Semi Synthetic 10W40:

API SJ

ACEA A2, B3

Packaging :

Delkol 15W40 SJ : 1 liter, 4 liters, can, drum, bulk

Delek Lubricants

P.O.B 31 Lod 71100 ISRAEL. Tel: 972-8-9270820, Fax: 972-8-8247072

www.deklelubes.com

Properties :

	Delkol SJ 20W50	DELKOL SJ 15W40
Viscosity Index (VI)	125	140
Specific Gravity at 15°C g/cc	0.890	0.880
Kinematic Viscosity @ 40°C, cSt	150	105
Kinematic Viscosity @ 100°C, cSt	17.5	14.3
Flash Pt., °C	230	225
Pour Pt., °C	-24	-24

