



Delo Silver oils are monograde diesel engine oils designed for a wide range of older diesel and petrol engines where a monograde is preferred. They are available in SAE 30 and 40 grades

### APPLICATIONS

- Marine, off-highway, agricultural and stationary plant operations.
- Hydraulics and transmissions, where appropriate
- The SAE 30 grade can be used in garden appliance petrol engines such as Briggs and Stratton.

**Not** recommended for use in any two cycle diesel engines, two cycle petrol engines or gas fuelled spark ignition engines.

### BENEFITS

- **Saves on maintenance**  
Metallo-organic anti-wear additive system resists wear by forming a protective layer on contact surfaces under all service conditions.
- **Prolongs periods between overhauls**  
Metallic detergent and ashless dispersant additive system resists the formation of high temperature deposits in diesel engines and low temperature sludge in petrol engines. Good oxidation stability resists oil degradation and protects against oil thickening, and oil line and filter plugging.
- **Preserves power and performance**  
Metallic detergent and ashless dispersant additive systems preserve power and performance by providing control of high-temperature piston and ring deposits.

### PERFORMANCE STANDARDS

API	CF
API	SJ



### TYPICAL CHARACTERISTICS

Product Code	2897	2898
SAE Grade	30	40
Density at 15°C, kg/L	0.87	0.87
Base No (D2896) mg KOH/g	6.8	6.7
Base No (D4739) mg KOH/g	9.2	9.2
Flash Point, COC, °C	>220	>225
Phosphorus, m%	0.085	0.085
Pour Point, °C	-39	-36
Sulfated Ash, %m	0.83	1.4
Viscosity, cSt at 40°C	90	124
Viscosity, cSt at 100°C	11.5	14.4
Viscosity Index	118	115
Zinc, m%	0.094	0.094

### PACK SIZES

1000L, 205L, 20L.

SAE 30 also available in 5L.

### ENVIRONMENT, HEALTH AND SAFETY

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

### OTHER INFORMATION

For further information on Caltex products and services call the Lubelink Advisory Service on 1300 364 169 between 8.00am and 6.00pm (EST) Monday to Friday.

Information in this publication is accurate at the time of printing and reasonable care has been taken to ensure it is complete and accurate. However, this information is subject to change (such as when formulations or usage and storage information changes). Please visit [www.caltex.com.au](http://www.caltex.com.au) for the latest product information. Independent advice should be sought before taking any action in reliance on the information in this publication, and Caltex Australia Limited and its related bodies corporate accept no liability for any reliance on this publication's content.