



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

LUBRIPLATE Dexron III/Mercon

Universal Automatic Transmission Fluid

LUBRIPLATE Dexron III/Mercon is a newly developed premium fluid fully qualified to cover current requirements for both General Motors and Ford. Dexron III is a General Motors trademark for qualified automatic transmission fluids. Mercon covers all automatic transmissions for Ford model year 1988 and after. LUBRIPLATE Dexron III/Mercon is designated as make-up and/or refill fluids to meet respective car warranties.

Outstanding features of LUBRIPLATE Dexron III/Mercon:

Superior Wear Prevention

Extensive Oxidation Stability

All Season Protection

Rust and Corrosion Resistant

Foam Resistant

Excellent Compatibility with Seals & Metal Components

Controlled Frictional Properties

Thermal Stability

General Motors Qualification No. F-30481

Ford Qualification No. M940507

LUBRIPLATE Dexron III/Mercon is also recommended for:

Allison C-4

Dexron II Fluids (Dexron IIE and Dexron IID)

Dexron Fluids

ATF Type "A" Suffix "A" Fluids

Ford M2C138CJ

Ford M2C166H

As well as Chrysler and American Motors cars, vans and light trucks plus those imported vehicles specifying Dexron II. This fluid can be used as a hydraulic fluid where specified by such manufacturers as Vickers and Sundstrand.

(over)

This product is not recommended to replace ATF Type "F" (ESE-M2C33F) or as a power steering fluid unless specified by the manufacturer.

Typical Tests

Viscosity @ 40°C	-	31 - 41 cSt
Viscosity @ 100°C	-	6.9 - 7.9 cSt
Brookfield @ -40°C	-	17,600 cP
Viscosity Index	-	190
API Gravity	-	31.2
Flash Point °C (°F)	-	185 (365)
Pour Point °C (°F)	-	-40 (-40)
Color	-	Red

Packaging Available

Part No.

Case, 12/1 Plastic Quarts	L0867-054
5 Gallon Pail	L0867-060
55 Gallon Drum	L0867-062

Printed in USA
Revised 6/16/11