



ATF Fluid

## DEXRON III

### Description of Product

**DEXRON III** contains a blend of superior base oils and a unique additive package to help extend the life of transmissions. It is formulated to maximize transmission performance, reduce transmission wear, and improve and maintain smooth shifting longer than conventional fluids. **DEXRON III** is compatible with new and rebuilt transmissions and will not void new car warranties. Recommended for use in GM, Ford, Mazda, Toyota, Chrysler and most import vehicles. It is also suitable for power steering Systems, Hydraulic applications and some manual transmissions where an automatic transmission fluid is specified..

### Features

- Contains long-life friction modifiers and premium base oils to help improve smooth shifting, eliminate slippage and shudder, prevent clutch wear and improve drivability longer than conventional fluids
- Contains high-performance seal conditioners to maintain and preserve the elasticity of seals to help prevent leaks
- Contains advanced anti-wear agents to provide wear protection for smoother shifts under all driving conditions
- Contains enhanced cleaning additives to help reduce varnish formation and keep the transmission running properly longer
- Engineered with a unique blend of viscosity modifiers and base oils to provide better oil flow at low temperatures and greater film protection at higher temperatures

### Meet the Specifications

FORD M2C138-CJ	FORD M2C166H	FORD MERCON	GM DEXRON IID
ALLISON C-4	GM DEXRON II-E	GM DEXRON III	
GM DEXRON II	GM TYPE A SUFFIX A	CAT. TO-2	

### Typical Characteristics:

DEXRON III	
Density at 15°C (g/cm <sup>3</sup> )	0.865
Kinematic Viscosity at 40°C (mm <sup>2</sup> /s)	33.0
Kinematic Viscosity at 100°C (mm <sup>2</sup> /s)	7.5
Viscosity Index	195
Flash Point (°C)	190
Pour Point (°C)	-48
Color	RED

### **Delek Lubricants**

P.O.B 31 Lod 71100 ISRAEL. Tel: 972-8-9270820, Fax: 972-8-8247072  
www.deklelubes.com