

Granville Diesel Gold 15W/40

5 Litre



Product Description

Granville Diesel Gold 15W/40 is a semi-synthetic engine oil for use in older engines requiring a lubricant of this grade.

Recommended for use by Granville for the following manufacturer's specifications

ACEA A3/B3
API SJ/CF
MB 229.1
VW 500.00
VW 505.00



* Image for illustrative purposes only.

Product Benefits

- * Ensures lubricant performance
- * Excellent high & low temperature performance
- * Outstanding fuel efficiency
- * Effective environmental protection

Product Usage

For engines where this specification lubricant is required.

Directions for Use

As recommended by the engine manufacturer.

Storage Instructions

Keep sealed in a cool, dry place.

Shelf Life

5 years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Specific Gravity	:	0.866 @ 15.6°C (typical)
Solubility	:	Insoluble
Flashpoint	:	>200°C
Kinematic Viscosity @ 40°C	:	111.3 cSt (typical)
Kinematic Viscosity @ 100°C	:	15.0 cSt (typical)

Size	Part No	Barcode
5 Litre	999V	5020618026617





TECHNICAL

Data

Granville Diesel Gold 15W/40 5 Litre



Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

Quality Lubricants

Quality Lubricants

Quality Lubricants

** The information contained in this leaflet is provided to enable the user to assess the product and should not be taken as a specification. All information provided is given in good faith, we can however not assume liability. It is up to the user to ensure that the information and the product is suitable for the use intended.*

Revision: 1 | Date: 16/03/2012

