



NESTE DIESEL 10W-30, 15W-40

Multigrade Diesel Engine Oils

SAE 10W-30 and 15W-40

API CG-4, CF-4, CF, CE, CD/SF

ACEA E2

Neste Diesel SAE 10W-30 and 15W-40 are made of selected paraffinic base oils blended with effective additives to prevent deposit and lacquer layer formation, wear and corrosion. Thanks to the multi-effect additives, they can be used in most diesel engines and also in gasoline engines.

TYPICAL CHARACTERISTICS	10W-30	15W-40
Densitykg/m ³ 15°C	865	885
Flash Point°C (COC)	240	230
Pour Point°C	-36	-33
Viscosity Index	138	134
ViscositycSt/ 40 °C	70	107
ViscositycSt/ 100 °C	10,6	14,1
ViscositycP/ °C	5500	5000
Pumpability °C	-35	-29
TBN mg KOH/g	about 10	about 10

Neste Diesel 10W-30 and 15W-40 are multigrade oils suitable for turbocharged heavy-duty diesel engines. Neste Diesel 10W-30 is excellent for winter use giving good fuel economy. Neste Diesel 15W-40 ensures reliable lubrication under heavy strain at high temperatures and reduces oil consumption. Neste Diesel 10W-30 and 15W-40 are multi-purpose oils which are also suitable for most gasoline engines; they can be used to rationalize substantially the grade range which needs to be stocked.

MIL-L-2104 E

Mack EO-J

Caterpillar TO-2

Allison C-3

Neste Markkinointi Oy

PL 95, 00095 NESTE OIL

www.neste.fi

Technical service

+358 200 11311

Updated 18.3.2015

Print

Close