



MULTIGRADE OIL FOR GASOLINE ENGINES

Product Description

DRAGON SJ is multi-grade engine oil for all gasoline engines. It suitable for recent technology engines (multi-valve, turbocharged, with/without catalytic converter) and vehicles requiring performance specification API SJ

Applications

- All gasoline engines, especially for most recent technology engines (multi-valve, turbocharged, with/without catalytic converter) supercharged or not, in cars
- Suitable for all journeys (in town, on highways) and particularly in severe conditions
- For all driving styles, vigorous speeds in all seasons

Features and potential benefits

- Meets API SJ and ILSAC GF-2(5W-30 and 10W-30) requirements, guarantee of an high and constant quality for lubricants
- Ensures easy cold start due to its extreme fluidity at low temperature and maintains a very resistant oil film even at extremely high operating temperature
- Gives the engine an excellent wear protection, develops performance and power.
- Keeps the engine's most sensitive parts clean thanks to its advanced detergent and dispersive additives.

Performance level

- API : API SJ
- ILSAC : GF-2 (5W-30, 10W-30)

Typical Properties

Test Items	Method	Unit	5W-30	10W-30	10W-40	20W-50
Specific gravity	ASTM D1298	-	0.8628	0.8692	0.8690	0.8842
Viscosity	40°C	ASTM D445	59.17	66.34	106.9	154.00
	100°C	ASTM D445	10.20	10.42	15.87	17.32
Viscosity index	ASTM D2270	-	161	145	159	121
Flash point	ASTM D92	°C	222	234	222	252
Pour point	ASTM D97	°C	-40	-40	-38	-25

S-OIL CORPORATION
192, Baekbeom-ro, Mapo-gu,
Seoul, 04196, Korea

DRAGON SJ
2016.2.25.

