



## MULTIGRADE OIL FOR GASOLINE ENGINES

### Product Description

DRAGON SL is multi-grade engine oil for all gasoline engines. It suitable for recent technology engines (multi-valve, turbocharged, with/without catalytic converter) and vehicles requiring performance specification API SL

### Applications

- All gasoline engines, especially for most recent technology engines (multi-valve, turbocharged, with/without catalytic converter) supercharged or not, in cars
- Suitable for all journeys (in town, on highways) and particularly in severe conditions
- For all driving styles, vigorous speeds in all seasons

### Features and potential benefits

- Meets API SL and ILSAC GF-3(5W-30) requirements, guarantee of an high and constant quality for lubricants
- Ensures easy cold start due to its extreme fluidity at low temperature and maintains a very resistant oil film even at extremely high operating temperature
- Protects mechanical parts and fully preserves the engine power, thus contributing to its youth and strength.

### Performance level

- API : API SL
- ILSAC : GF-3 (5W-30)

### Typical Properties

Test Items	Method	Unit	5W-30	10W-40	20W-50
Specific gravity	ASTM D1298	-	0.8603	0.8692	0.8797
Viscosity 40°C	ASTM D445	cSt	62.94	106.9	169.9
Viscosity 100°C	ASTM D445	cSt	10.72	15.88	19.16
Viscosity index	ASTM D2270	-	161	159	128
Flash point	ASTM D92	°C	228	222	248
Pour point	ASTM D97	°C	-40	-39	-28

S-OIL CORPORATION  
192, Baekbeom-ro, Mapo-gu,  
Seoul, 04196, Korea

DRAGON SL  
2016.02.25.



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet is obtainable via your commercial adviser.