



MULTIGRADE OIL FOR GASOLINE ENGINES

Product Description

DRAGON SM is multi-grade engine oil for all gasoline engines. It suitable for recent technology engines (multivalve, turbocharged, with/without catalytic converter) and vehicles requiring performance specification API SM

Applications

- O All gasoline engines, especially for most recent technology engines (multi-valve, turbocharged, with/without catalytic converter) supercharged or not, in cars
- O Suitable for all journeys (in town, on highways) and particularly in severe conditions
- For all driving styles, vigorous speeds in all seasons

Features and potential benefits

- O Meets API SM requirements, guarantee of an high and constant quality for lubricants
- O Ensures easy cold start due to its extreme fluidity at low temperature and maintains a very resistant oil film even at extremely high operating temperature
- O Protects mechanical parts and fully preserves the engine power, thus contributing to its youth and strength.

Performance level

O API: API SM

Typical Properties

| Test Items | Method | Unit | 10W-40 |
|------------------|------------|------------|--------|
| Specific gravity | ASTM D1298 | - | 0.790 |
| Viscosity 40°C | ASTM D445 | cSt | 99.42 |
| 100℃ | ASTM D445 | cSt | 14.62 |
| Viscosity index | ASTM D2270 | - | 153 |
| Flash point | ASTM D92 | $^{\circ}$ | 234 |
| Pour point | ASTM D97 | °C | -37.5 |

S-OIL CORPORATION 192, Baekbeom-ro, Mapo-gu, Seoul, 04196, Korea

DRAGON SM 2016.2.04.





