

## Product Information

# DUPLEX CDX 15W-40

---

### Description

Duplex CDX 15W-40 is a mixed fleet lubricant, incorporating high quality minerals oils and performance additives, suitable for use in a wide variety of diesel and petrol engine designs, including turbocharged versions. This grade will protect engine components from rust and corrosion and provide high levels of engine cleanliness, even in extended oil drain applications.

### Applications

Duplex CDX 15W-40 can be used in a range of vehicle and engine types, including commercial vehicles, buses, coaches, cars and vans, plant, construction and agricultural machinery. Duplex CDX 15W-40 may also be used in transmissions, hydraulic systems, PTOs, compressors, etc. where a product of this type and specification is required.

### Performance Levels

API CG-4 / CF / SL / SJ  
Mercedes Benz 229.1  
Mercedes Benz 228.1  
MAN 271  
Mack EO-L  
Volvo VDS2  
VW 505.00  
Allison C4

### Physical Characteristics

Density at 15 °C	0.884
Kinematic Viscosity at 100 °C, cSt	14.4
Kinematic Viscosity at 40 °C, cSt	106
Viscosity Index	135
Flash Point (closed) °C	190
Sulphated Ash (%Wt)	1.3
Pour Point, °C	-30
TBN	10.0

(TDS Duplex CDX 15W-40 – 140714 Issue 15)



Certificate No. FM 21756



Certificate No. EMS 60044



Certificate No. OHS 555083

Morris Lubricants, Castle Foregate,  
Shrewsbury, Shropshire, SY1 2EL  
Telephone (01743) 232200  
Fax (01743) 353584