

Product Information

A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.



Lubricants - Engine Oil – Motorcycle Motor Oils

Version: 302/04

DuraBlend™ 2T Motorcycle Oil

High performance semi-synthetic low-smoke motor oil for all 2-cycle motorcycle engines – Provides optimum performance, helps keep the engine clean, prevents scuffing and ring sticking.

DuraBlend 2T is a high performance synthetic blend low-smoke motor oil for all 2-cycle motorcycle engines. DuraBlend 2T is specially formulated to meet the requirements of **all leading motorcycle manufacturers**.

Approvals/Performance levels

SAE
API: TC
JASO: FD
ISO: L-EGD

Applications

High performance synthetic blend low-smoke motor oil for all 2-cycle motorcycle engines.

Pre-diluted for easier mixing and can be used for both injector *and* pre-mix applications.

Fuel/oil ratios as specified by the engine manufacturer up to a maximum of 100:1.

Can be used in virtually all 2-stroke motorcycle engines including two-stroke injection systems and pre-mix systems.

Features and Benefits

Wear protection

Strong oil film protects the engine against wear and corrosion.

Engine cleanliness

Improved piston cleanliness prevents scuffing and ring sticking.

Environment

Low smoke motor oil burns up ashless.

Break Down resistance

Thermal and oxidation stable oil film provides greater resistance to oil breakdown.

Multi Purpose use

Suitable for racing, motocross, enduro applications.

Product Information

A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.



Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. A Material and Safety Data Sheet (MSDS) is available on request via your local sales office or via the internet @ <http://msds.ashland.com>

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

DuraBlend 2T	
SAE Viscosity Grade	
Viscosity, mm ² /s @ 100 °C. ASTM D-445	9.4
Viscosity, mm ² /s @ 40 °C. ASTM D-445	60
Viscosity Index ASTM D-2270	140
TBN, mg KOH/g ASTM D-2896	3.1
Pour Point, °C ASTM D-5950	-42
Specific Gravity @ 15.6°C. ASTM D-4052	0.867
Flash Point, COC, °C. ASTM D-92	90

This information only applies to products manufactured in the following location(s): Europe

People Who Know, Use Valvoline™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineurope.com

Author:

AdG

Replaces – 302/03

*Trademark owned by a third party ™ Trademark of Ashland or its subsidiaries, registered in various countries © 2011, Ashland

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ashland Inc. and its subsidiaries assume legal responsibility.