

Product Information

A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.



Lubricants - Engine Oil – Motorcycle Motor Oils

Version: 303/06

DuraBlend™ Scooter 2T Motor Oil

High performance synthetic blend low-smoke motor oil for all 2-cycle scooter engines -- Specially formulated to meet the requirements of all leading scooter manufacturers.

DuraBlend Scooter 2T is specially formulated to provide optimum performance and prevents scuffing and ring sticking. The product meets the requirements of all leading scooter manufacturers.

Approvals/Performance levels

SAE
API: TC
JASO: FD
ISO: L-EGD

Applications

High performance synthetic blend low-smoke motor oil for virtually all 2-cycle motor scooter engines.

Pre-diluted for easier mixing and may be used for both injector and pre-mix applications.

Use fuel/oil ratios as specified by the engine manufacturer up to a maximum of 100:1.

Features and Benefits

Wear protection

Increased anti-wear agents help minimize wear from metal-to-metal contact.

Engine cleanliness

Special cleaning agents and dispersants help prevent deposit formation, guard against scuffing and ring sticking to keep engine clean.

Environment

Low smoke motor oil burns up ashless.

Breakdown resistance

Shear stable viscosity improvers help resist oil film breakdown.

Multi-purpose use

Suitable for leisure, transport, rally, day-to-day riding.



Product Information

A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. A Safety Data Sheet (SDS) is available on request via your local sales office or via the internet @ <http://msds.ashland.com>

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

DuraBlend Scooter 2T	
SAE Viscosity Grade	
Viscosity, mm ² /s @ 100 °C. ASTM D-445	9,3
Viscosity, mm ² /s @ 40 °C. ASTM D-445	59
Viscosity Index ASTM D-2270	140
TBN, mg KOH/g ASTM D-2896	1,4
Pour Point, °C ASTM D-5950	-42
Specific Gravity @ 15.6°C. ASTM D-4052	0,858
Flash Point, COC, °C. ASTM D-92	80

This information only applies to products manufactured in the following location(s):
Europe

Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineeurope.com

Author:

AdG

Replaces – 303/05

*Trademark owned by a third party ™ Trademark of Ashland or its subsidiaries, registered in various countries © 2014, Ashland

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ashland Inc. and its subsidiaries assume legal responsibility.