



Mobil EAL EnviroSyn H Series

Hydraulic Fluids

Product Description

Mobil EAL EnviroSyn H Series oils are super premium, high performance fully synthetic environmentally aware hydraulic and circulating oils designed to provide outstanding performance in systems operating at moderate to severe conditions. They provide excellent wide temperature range performance above and beyond the capabilities of non-synthetic environmentally aware oils. Mobil EAL EnviroSyn H Series provides exceptional anti-wear and film strength characteristics necessary for hydraulic systems operating under high load and high pressures. This is verified by their excellent wear control in the ASTM D 2882 and Vickers 35VQ25 Pump Wear Tests. Their 12-stage rating in the FZG Gear Load Test demonstrates a high level of protection against wear and scuffing and the suitability of this product to protect gears and bearings used in conjunction with hydraulic systems. The Mobil EAL EnviroSyn H Series provide excellent protection against corrosion and ensures very good multi-metal compatibility allowing its use in systems employing various metallurgy that may be used in pump and component design. They also provide very good thin oil film protection against rusting. In addition to their exceptional performance capability, they satisfy the requirements for ready biodegradability and non-toxicity making them a desirable product for severe operating conditions where leakage or spillage of conventional oils could result in damage to the environment.

Mobil EAL EnviroSyn H Series oils are formulated from select, high-quality, high-VI synthetic base oil materials and high technology additive system specifically engineered to meet or exceed the performance requirements of most hydraulic pump and system builders while satisfying the stringent criteria for biodegradability and toxicity. Compared to the best vegetable oil-based and synthetic ester based hydraulic oils, these products provide improved oxidation stability and anti-foam performance, together with improved high and low temperature performance (-20° F to 200° F).

Features and Benefits

Mobil EAL EnviroSyn H Series oils provide excellent wide temperature range performance. Their exceptional anti-wear, lubricity, and film strength characteristics assure performance in hydraulic and circulation systems operating under moderate to severe conditions. The ready biodegradability and virtually non-toxic nature of these products make them an excellent choice where leakage or spillage could enter environmentally sensitive areas. The inadvertent leakage or spillage of this product in environmentally sensitive areas could result in easier clean-up and lower remediation costs.

Features	Advantages and Potential Benefits
Ready Biodegradability and Non-Toxicity	Reduces potential for environmental damage
	Lowers potential remediation and clean-up costs caused by spills or leakage
	Becomes an integral part of plant environmental programs
Excellent Wide-Temperature Range Performance	Assures high level system lubrication at high and low temperatures
High Oxidation Stability	Long oil life
	Reduced deposit and sludge formation
	Extended filter life
Outstanding Load-Carrying and Anti-Wear Properties	Protects system components against wear and scuffing Provides long equipment life
Exceptional Corrosion Protection	Reduces corrosion of internal system components
Excellent Multi-Metal Compatibility	Will not react with steel or copper alloys
Good Elastomer Compatibility	Works well with same elastomers used with conventional mineral based oils. No need for special seals or elastomers

Applications

- Hydraulic systems where spills or leakage could result in damage to the environment

- In systems where readily biodegradable and virtually non-toxic fluids may be required
- Circulation systems containing gears and bearings where mild extreme-pressure characteristics are desired
- Systems containing servo-valves
- Hydraulic systems operating with oil temperatures in the range of -20F to 200F
- Marine and mobile equipment operating in environmentally sensitive areas
- Circulation systems operating under mild to moderate service conditions
- Industrial hydraulic systems where leaked or spilled fluids could get into plant effluent
- Air line oilers and some limited oil-mist generating systems
- Air-over-hydraulic fluid systems operating in environmentally sensitive areas

Specifications and Approvals

According to ExxonMobil, Mobil EAL

EnviroSyn H Series is of the following quality level:

	32	46	68	100
Vickers I-286-S		X	X	
Vickers M-2950-S		X	X	

Mobil EAL EnviroSyn H Series is also recommended for use in applications requiring:

	32	46	68	100
Environmentally friendly characteristics	X	X	X	X
Anti-wear protection	X	X	X	X
Compatibility with system components	X	X	X	X

Typical Properties

Mobil EAL EnviroSyn H Series

ISO Viscosity Grade	32	46	68	100
Viscosity, ASTM D 445				
cSt @ 40°C	33.1	48.8	69	98.9
cSt @ 100°C	6.36	7.8	10.1	13.5
Viscosity Index, ASTM D 2270	147	145	138	136
Density @ 15° C, ASTM D4052, kg/L	0.869	0.874	0.884	0.914
FZG Gear Test, DIN 51354, Fail Stage	12	12	12	12
Rust Characteristics, procedure B, ASTM D 665	Pass	Pass	Pass	Pass
Pour Point, °C, ASTM D 97	-39	-45	-39	-42
Flash Point, °C, ASTM D 92	268	260	266	279
Biodegradability, CO2 Conversion, EPA 560/6-82-003, %	>60	>60	>60	>60
Aquatic Toxicity, LC50, Trout, OECD 203, ppm	>5000	>5000	>5000	>5000

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and EnviroSyn are trademarks of ExxonMobil Corporation, or one of its subsidiaries.

1-2011

Exxon Mobil Corporation
22777 Springwoods Village Parkway
Spring TX 77389

1-800-ASK MOBIL (275-6624)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com. ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Copyright © 2001-2015 Exxon Mobil Corporation. All rights reserved.