



Product Information:

ECOTRANS 75W-80

HEAVY DUTY TRANSMISSION OIL

Description

Ecotrans 75W-80 is a fully synthetic high performance transmission fluid, developed for use in ZF manual and automated manual transmission (AMT) systems. The product not only offers a high level of component protection under a wide range of operating conditions and loads, but improved gear shift and improvements in fuel economy.

Features and Benefits

- Improved gear shift performance
- Protects components under high load conditions
- Improved transmission efficiency with potential fuel savings
- High temperature stability during sustained long distance schedules

Applications

Ecotrans 75W-80 can be used in ZF manual and automated manual transmission (AMT) systems fitted to commercial vehicles, light commercial vehicles, coaches and buses, where one of the specifications below is listed. The versatility of Ecotrans 75W-80 allows it to be used in any other types of transmission system requiring an API GL4 lubricant of this viscosity grade.

Performance Level

API GL- 4

MAN 341 Type E3, Z-4

Volvo 97305

ZF TE ML 01L, 02L, 08, 13*,16K

Can be used in DAF, Eaton and Iveco transmissions where a product of this type is specified.

*where ZF TE-ML 13 stipulates ZF TE-ML 02L

Physical Characteristics

Viscosity @ 100°C, cSt. 9.385

Viscosity @ 40°C, cSt. 55.58

Viscosity Index 152

Flash Point, Closed (°C) 150

Pour Point (°C) -33

Figures based on average productin values.

Part No.s: ECT025, ECT205

(TDS Ecotrans 75W-80 – 170915 Issue 5)

