

## El Mar® 2000

Conoco® El Mar 2000 is a high-quality, very low-ash, dispersant-detergent gas engine oil designed for use in naturally aspirated and moderately turbocharged, low- to medium-speed 2-stroke cycle and 4-stroke cycle natural gas engines.

El Mar 2000 is formulated with field-proven performance additives to meet the rigorous lubrication demands of modern, fuel-efficient, low-emission gas engines. It provides excellent resistance to oxidation and nitration, protects against ring and liner wear, helps minimize engine sludge and piston deposits for excellent engine cleanliness, and protects against corrosion. It provides excellent deposit control to keep ports clean on 2-stroke cycle engines and to help both 2-stroke cycle and 4-stroke cycle gas engines operate at peak performance.

### ***Applications***

- Low- to medium-speed, 2-stroke cycle gas engines where port plugging is a concern
- Low- to medium-speed, naturally aspirated 4-stroke cycle gas engines
- Medium-speed, 4-stroke cycle gas engines operating under moderate loads

El Mar 2000 is recommended for use in natural gas engines manufactured by:

- Ajax
- Allis Chalmers
- Cooper Bessemer
- Cooper Superior
- Dresser Clark
- Dresser Rand (Category I & II)
- International Harvester
- Minneapolis-Moline
- Waukesha

### ***Features/Benefits***

- Field-proven performance in providing excellent engine cleanliness
- Good dispersancy protects against sludge and varnish formation
- Low-ash formulation helps minimize port deposits
- Excellent resistance to oxidation and nitration
- Protects against scuffing and wear
- Protects against rust and corrosion

**Very Low-Ash  
Natural Gas  
Engine Oil**

### **CONTACT INFORMATION**

**Phillips66  
Lubricants.com**

U.S. Customer  
Service:  
**1-800-368-7128**

Technical Hotline:  
**1-877-445-9198**

International  
Customer Service:  
**1-832-765-2500**

E-mail address:  
**conocolubricants@  
p66.com**



- Does not contain any bright stock, which can cause harmful carbon deposits

### El Mar® 2000

#### Typical Properties

SAE Grade	30	40	15W-40
Specific Gravity @ 60°F	0.884	0.888	0.869
Density, lbs/gal @ 60°F	7.36	7.39	7.24
Color, ASTM D1500	3.5	3.5	3.0
Flash Point (COC), °C (°F)	260 (500)	280 (536)	233 (451)
Pour Point, °C (°F)	-30 (-22)	-30 (-22)	-39 (-38)
Viscosity, Kinematic			
cSt @ 40°C	92.0	149	103
cSt @ 100°C	10.8	14.4	14.0
Viscosity Index	101	94	138
Cold Cranking Viscosity, cP	—	—	6,100
@ (°C)	—	—	(-20)
Sulfated Ash, ASTM D874, wt %	0.14	0.14	0.14
Total Base Number (TBN), ASTM D2896	2.4	2.4	2.4

### Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3apps.phillips66.com/NetMSDS>.