



Sasol Engine Oil 2-Stroke

SELF-MIXING OIL, TWO-STROKE ENGINE, GRADE 120

Description

Sasol Engine Oil 2-Stroke is a specially formulated, self-mixing 2-stroke engine oil having low ash-forming properties to prevent plug fouling and ring sticking.

Application

Because of its excellent thermal stability Sasol Engine Oil 2-Stroke is particularly recommended for high temperature applications such as high-output, air-cooled engines.

Sasol Engine Oil 2-Stroke is suitable for use in 2-stroke engines of

- all motorcycles, mopeds and scooters
- chain saws
- lawn mowers
- generators

that are lubricated either by autolube systems or petroil mixtures.

Sasol Engine Oil 2-Stroke is NOT intended for outboard motors.

Features and Benefits

The engine manufacturer's recommendations must be adhered to when preparing petroil mixtures. Sasol Engine Oil 2-Stroke is dyed green for ease of identification when added to fuels. To indicate, therefore, whether it is pure petrol or a mixture, the mixture is green and not red, orange or yellow.

Product Specifications

API TC
Jaso FC/ISO GD



Typical Characteristics

| Property | Units | Typical |
|---------------------------|--------------------|----------------|
| Viscosity @ 40°C | mm ² /s | 68 |
| Base Oil Viscosity @ 40°C | mm ² /s | 130 |
| Pour Point | °C | -6 |
| Flash Point (PMCC) | °C | 105 |
| Carbon Residue | % m/m | 0,3 |
| Oil Content | % m/m | 85 |
| Solvent | % m/m | 10 |
| Sulphated Ash | % m/m | 0,1 |
| Density @ 20°C | kg/m ³ | 878 |

Storage and Handling

Use PVC, nitrile or other oil resistant gloves and protective clothing to prevent skin contact. Where eye contact is a potential hazard, goggles should be worn.

Avoid temperatures exceeding 80°C.

Avoid temperatures above 80°C and strong oxidizing agents.

Ambient temperatures and atmospheric pressures normally encountered within buildings or roofed-over outdoor storage areas are acceptable. Avoid entering areas where mists or vapours have built up as a result of abnormal temperatures or pressures without the proper breathing equipment and protective clothing.

Pack Information

| <u>Product Code</u> | <u>Pack Size</u> |
|----------------------------|-------------------------|
| | 1x200 ml |
| | 1x500 ml |
| | 50x200 ml |
| | 20x500 ml |
| | 20 L |
| | 210 L |