



## *Sasol Engine Oil Multigrade F 20W-50* *ENGINE OIL, MULTIGRADE 150 (SAE 20W-50)*

### *Description*

Sasol Engine Oil Multigrade F 20W-50 is a multigrade, medium-duty, internal combustion engine oil formulated with high-performance additives.

### *Application*

Sasol Engine Oil Multigrade F 20W-50 is suitable for use in all engines operating under the API service conditions below SF-CC.

### *Features and Benefits*

Sasol Engine Oil Multigrade F 20W-50 has the following features and benefits:

- achieve multigrade properties and low oil consumption
- comply with the lubrication requirements of the majority of passenger and light commercial vehicles
- ensure good cold starting properties

Sasol Engine Oil Multigrade F 20W-50 can also be used as a gear lubricant for manual transmissions which do not require extreme pressure oils.

### *Product Specifications*

API CC & SF

SANS 1361



### Typical Characteristics

Property	Units	Typical	ASTM	IP
Viscosity			D445	71
@ 100°C	mm <sup>2</sup> /s	<b>18</b>		
@ 40°C	mm <sup>2</sup> /s	<b>170</b>		
Apparent Viscosity	mPa.s @ -10°C	<b>3700</b>	D5293	
Viscosity Index		<b>125</b>	D2270	226
Pour Point	°C	<b>-21</b>	D97	15
Flash Point (COC)	°C	<b>240</b>	D92	36
Evaporative Loss (Noack)	% m/m	<b>5,5</b>	CEC L-40-T-87 or DIN 51581	
Density @ 20°C	kg/m <sup>3</sup>	<b>888</b>	D4052	365
Sulphated Ash	% m/m	<b>0,22</b>	D874	163
Total Base Number	mg KOH/g	<b>7,7</b>	D2896	276

### Storage and Handling

Use PVC, nitrile or other oil resistant gloves and protective clothing to prevent skin contact. Where eye contact is a potential hazard, goggles should be worn.

Avoid temperatures above 80°C and strong oxidizing agents.

Ambient temperatures and atmospheric pressures normally encountered within buildings or roofed-over outdoor storage areas are acceptable. Avoid entering areas where mists or vapours have built up as a result of abnormal temperatures or pressures without the proper breathing equipment and protective clothing.

### Pack Information

Product Code	Pack Size
	1x5 L
	1x500 ml
	20x500 ml
	4x5 L (Plastic)
	20 L
	210 L