

Granville EP 75W/80

1 Litre & 5 Litre



Product Description

EP 75W/80 is formulated to the specific requirements of manual gearboxes requiring this grade. EP 75W/80 is formulated using high quality base oils and extreme pressure gear oil additives ensuring outstanding anti-wear characteristics.

Recommended for use by Granville for the following manufacturer's specifications

API GL-4
GM 1940768
MIL-L-2105 D
PSA B712330
Volvo 97308



* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	1638	5020618016380
5 Litre	1717	5020618017172

Product Benefits

- * Excellent oxidation stability
- * Outstanding low & high temperature performance
- * Ensures the synchromesh functions correctly
- * Protect against corrosion
- * Long life
- * Excellent wear protection

Product Usage

For gearboxes that require EP 75W/80 lubricant

Directions for Use

Use as per the manufacturers recommendations

Storage Instructions

Keep sealed in a cool dry place

Shelf Life

5 years from date of manufacture

Specification Information

API: GL 4
Military: Mil-L-2105

Appearance : Amber fluid

Revision: 1 | Date: 16/03/2012





TECHNICAL

Data

Granville EP 75W/80

1 Litre & 5 Litre



Odour	: Characteristic
Specific Gravity	: 0.884 @ 15.6°C
Solubility	: Insoluble in water
Flashpoint	: 225°C
Kinematic Viscosity @ 40°C	: 97.4 cSt (typical)

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

Quality Lubricants

Quality Lubricants

Quality Lubricants

** The information contained in this leaflet is provided to enable the user to assess the product and should not be taken as a specification. All information provided is given in good faith, we can however not assume liability. It is up to the user to ensure that the information and the product is suitable for the use intended.*

Revision: 1 | Date: 16/03/2012

