

# FLEXWAY P 68

## Process oil

### Product description

FLEXWAY P 68 is a high-quality process oil made of highly refined, paraffin-based mineral oil. The product is extremely stable and has a very wide area of application.

### Application areas

Within industry, highly refined mineral oils are used to a large extent for purposes other than lubrication. These oils are known as process oils and can be included as a component in plastic, rubber, etc., or be used as a process aid. FLEXWAY P 68 can be used for example as a plasticiser and filler in the manufacture of rubber and plastic. The product also works very well as a process aid for e.g. binding dust or working as a wetting agent in the roofing felt industry.

### Characteristics and advantages

FLEXWAY P 68 is a high-quality process oil made of highly refined, paraffin-based mineral oil. The product is characterised by high stability, low volatility, a low tendency to change colour and a high natural viscosity index.

### Tests and approvals

### Handling and storage

Avoid skin contact. In the event of contact with skin, wash with soap and water. Dispose of used oil at a recycling station or equivalent. Safety data sheets are available on [www.statoillubricants.com](http://www.statoillubricants.com) or supplied on request.

### Typical Data

Characteristics	Typical value	Unit	Method
Density at 15°C	878	kg/m <sup>3</sup>	ISO 12185
Pour point	-	°C	ISO 3016
Viscosity at 40°C	68.0	mm <sup>2</sup> / s	ISO 3104

Revision date 18-Aug-2014