

FLUIDE AT 42



AUTOMATIC TRANSMISSION FLUID

USES

- Automatic or semi-automatic transmissions and torque converters of passenger cars, light commercial vehicles and industrial vehicles, when the manufacturer requires an ATF (Automatic Transmission Fluid) GM DEXRON® - III.
- Suitable for use in transmissions of trucks, buses and public works machineries when a fluid type ALLISON C4 is required.
- Hydraulic systems when a fluid type GM DEXRON® - III is required.

PROPERTIES

- Very high viscosity index linked with an excellent viscosity stability in operation.
- Very low pour point.
- Very good thermal stability.
- Excellent resistance to oxidation.

CHARACTERISTICS

FLUIDE AT 42	Unit	
Volumetric mass at 15°C	kg/m ³	860
Colour	-	Red
Viscosity at 40°C	mm ² /s	34
Viscosity at 100°C	mm ² /s	7.7
Viscosity index	-	207
Viscosity Brookfield at -40°C	mPa.s	13 300
Flash point Cleveland	°C	196
Pour point	°C	-51

The typical characteristics mentioned represent mean values.

PERFORMANCES

ALLISON C4 n° C4-24842997
BMW group 24 - 3.0
FORD MERCON®
DEXRON® - III
MAN 339 type V-1 (ex MAN 339 Type F)
MAN 339 type Z-1 (ex MAN 339 Type F)

PSA PEUGEOT CITROEN (4HP14, 4HP18, 4HP20)
VOITH H 55.633535
ZF TE-ML 02F, 03D, 04D, 09, 11B, 14A, 17C
MB-Approval 236.1
NISSAN

TOTAL LUBRIFIANTS

Le SPAZIO
562 Avenue du Parc de l'Ile
92029 - NANTERRE CEDEX

FLUIDE AT 42
January 2013



This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute a special hazard.
A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant