


# FM GEAR OIL TLS 150

## Product Information

Speciality gear fluid for use in food manufacturing equipment



**FM GEAR OIL TLS 150** is a speciality anti-wear gear fluid which is specifically designed for use in the food and beverage canning industry.

It is based on a careful blend of fluids and selected additives chosen for their ability to meet the stringent requirements of the food industry.

Certified by NSF for ISO 21469 and registered by NSF (Class H1) for use where there is potential for incidental food contact. Produced according to FLT Quality Standards, in facilities where HACCP audit and Good Manufacturing Practice have been implemented and form part of the quality and hygiene management systems ISO 9001 and ISO 21469.

### CERTIFICATIONS AND SPECIFICATIONS

- NSF H1
- NSF ISO 21469
- Kosher
- Halal
- DIN 51517 CLP



## PERFORMANCE FEATURES

- The base fluid has been selected for its ability to provide superior lubrication under variety of applications
- Specially formulated to provide good lubrication even when operating in locations where it is subject to contamination with water, juice and food, which is held in suspension, thus protecting metal surfaces from wear and corrosion.
- Neutral odour and taste
- Good anti-oxidant properties. Resists the formation of deposits and sludge even at elevated temperatures, resulting in long equipment life

## APPLICATIONS

- Lubrication of rotary can seaming machines equipped with total loss systems
- Circulating and bearing oil systems where contamination with water or food juice can occur, such as citrus juice extraction machines
- Can be used on drives and transport chains in the food Industry. Easily applied by either brush, through baths or by automatic lubrication system

## SEAL AND PAINT COMPATIBILITY


Compatible with the elastomers, gaskets, seals and paints, such as poly-urethane and two part epoxy resin paints, frequently used on machinery and in lubrication systems employed in the food processing industry.

## HANDLING AND STORAGE

All food grade lubricants should be stored separately from other lubricants, chemical substances and foodstuffs and out of direct sunlight or other heat sources. Store between 0 °C and +40 °C. Provided that the product has been stored under these conditions we recommend to use the product within 5 years from the date of manufacture. Upon opening a pack, the product must be used within 2 years (or within 5 years of date of manufacture, whichever is the sooner).

### TYPICAL CHARACTERISTICS (Typical for current production. Variations in these characteristics may occur.)

			FM GEAR OIL TLS 150
Property	Test Method		
NSF Reg. No.			144717
Colour			Colourless / slight pale
Density at +15 °C	kg/m <sup>3</sup>	ISO 12185	873
Flashpoint	°C	ISO 2592	263
Pourpoint	°C	ISO 3016	-12
Kin. Visc. at +40 °C	mm <sup>2</sup> /s	ISO 3104	150
Kin. Visc. at +100 °C	mm <sup>2</sup> /s	ISO 3104	15,1
Viscosity index	ISO 2909		104
FZG-Test A/8.3/90 Failure Load Stage	ISO 14635-1		>12



**FUCHS LUBRITECH GMBH**  
Werner-Heisenberg-Straße 1  
67661 Kaiserslautern / Germany  
T: +49 (0) 6301 3206-0 / F: +49 (0) 6301 3206-940  
[www.fuchs-lubritech.com](http://www.fuchs-lubritech.com)

 A Member of the  
FUCHS PETROLUB Group

As far as we know these information reflect the current state of knowledge and our research. They cannot, however, be taken as an assurance about the properties nor as a guarantee of the suitability of the product for the individual case in point. Before using our products the purchaser must, therefore, check the suitability and be satisfied that the output will be satisfactory. Our products are continually being up-dated. We reserve the right, therefore, to alter the information of this product information at any time and without prior announcement. We are specialized in developing products for extreme tribological problems in cooperation with end users. FUCHS LUBRITECH provides service and individual advice. Please contact us! E-Mail: [cassida.lubricants@fuchs-lubritech.de](mailto:cassida.lubricants@fuchs-lubritech.de)