

# Q8 Formula Exclusive C1 5W-30

## Description

Ultra High Performance Low SAPS SAE 5W-30 Synthetic Engine Oil for Ford Euro 4 & Euro 5 passenger car engines.

## Application

- Engine oil for passenger cars with normally aspirated or turbo-charged gasoline, LPG or diesel Euro 4 & Euro 5 engines requiring LowSAPS engine oil.
- Specially developed for Euro 4 & Euro 5 Ford M2C 934-B applications.
- Backward compatible with Ford M2C 912 & 913A/B applications.
- For Mazda cars with a Euro 4 diesel engine equipped with a DPF.

## Recommendations

- Only for Euro 4 & Euro 5 engines requiring Low SAPS engine oil.

## Specifications

- ACEA C1
- Ford M2C 934-B
- Ford M2C 912 & 913A/B
- Recommended for Mazda cars with Euro 4 & Euro 5 diesel engines equipped with a DPF.

Properties	Method	Unit	Typical
Viscosity Grade			SAE 5W-30
Density, 15 °C	D 4052	kg/m <sup>3</sup>	851
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	10.2
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	57
Viscosity Index	D 2270	-	168
Apparent Viscosity, -30 °C	D 5293	mPa.s	4780
Pour Point	D 97	°C	-30
Flash Point	D 92	°C	226
Viscosity at high temp. & high shear rate	CEC-L-36-A-90	mPa.s	>=2.9

*The figures above are not a specification. They are typical figures obtained within production tolerances.*

