

Q8 Formula MX Long Life 5W-30

Description

Ultra High Performance Low SAPS SAE 5W-30 Synthetic Engine Oil for Euro 5 and Euro 6 engines for normal and extended drain intervals.

Application

- Engine oil for passenger cars and commercial vehicles with normally aspirated or turbo-charged gasoline, LPG or diesel Euro 5 and Euro 6 engines requiring LowSAPS engine oil.
- Specially developed for Mercedes-Benz engines requiring MB 229.52 engine oil specification.
- Backward compatible with Mercedes-Benz engines requiring MB 229.51 and MB 229.31 engine oil specifications.
- ACEA C2 for Peugeot Citroen engines

Specifications

- ACEA C3
- ACEA C2
- API SN
- MB 229.52, 229.51, 229.31
- GM Dexos 2 level

Benefits

- Synthetic engine lubricant designed for Mercedes-Benz passenger car engines for Euro 5 & Euro 6 models.
- Best in-class biofuel compatibility due to excellent oxidation stability and optimized cold flow properties
- LowSAPS formulation protecting SCR catalyst and Diesel Particulate Filter.
- Excellent engine cleanliness and wear protection increasing engine durability.
- Reduces fuel consumption.
- For extended oil drain intervals.

Properties	Method	Unit	Typical
Viscosity Grade			SAE 5W-30
Absolute Density, 15 °C	D 4052	kg/m ³	852
Kinematic Viscosity, 100 °C	D 445	mm ² /s	12.4
Kinematic Viscosity, 40 °C	D 445	mm ² /s	73.8
Viscosity Index	D 2270	-	171
Apparent Viscosity, -30 °C	D 5293	mPa.s	5700
Sulphated Ash	D 280	% mass	0.8
Pour Point	D 97	°C	-42
Flash Point	D 92	°C	210

The figures above are not a specification. They are typical figures obtained within production tolerances.

