

# Q8 Formula Plus 15W-40

## Description

High Performance Engine Oil

## Application

- High quality mineral engine oil for passenger cars and vans with gasoline or LPG engines.
- Suitable for engines with catalyst and normally aspirated and turbocharged diesel engines.

## Specifications

- ACEA A3/B3
- API SL/CF
- VW 501.01/505.00
- MB 229.1

## Benefits

- Retains high viscosity index for excellent lubrication
- Protect against wear
- Keeps engine clean
- Protection against rust and corrosion
- Prevents formation of black sludge

Properties	Method	Unit	Typical
Viscosity Grade			SAE 15W-40
Absolute Density, 15 °C	D 4052	kg/m <sup>3</sup>	884
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	14.2
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	107.7
Viscosity Index	D 2270	-	134
Apparent Viscosity, -20 °C	IP 383	mPa.s	6700
Borderline Pumping Temperature	D 3829	°C	-26.5
Pour Point	D 97	°C	-27
Flash Point	D 93	°C	202
Viscosity at high temp. & high shear rate	CEC-L-36-A-90	mPa.s	>=3.5

The figures above are not a specification. They are typical figures obtained within production tolerances.

