

Q8 Formula Select C2 0W-30

Description

High Performance Low SAPS SAE 0W-30 Synthetic Engine Oil for Toyota and Peugeot Citroën Euro 4 & Euro 5 engines equipped with or without DPF

Application

- Engine oil for passenger cars and commercial vehicles with normally aspirated or turbo-charged gasoline, LPG or diesel Euro 4 & Euro 5 engines requiring LowSAPS engine oil.
- Specially developed for Toyota and Peugeot Citroën Euro 4 & Euro 5 engines.
- Backward compatible with Peugeot Citroën engines requiring ACEA A1/B1 and ACEA A5/B5 engine oil specification.

Specifications

- ACEA C2
- Meets the specification of Fiat 9.55535 GS1

Benefits

- Ultra robust formulation due to synthetic formulation technology.
- Reduces fuel consumption.
- LowSAPS formulation protecting Exhaust Catalyst and Diesel Particulate Filter.
- Excellent engine cleanliness and wear protection increasing engine durability.
- Excellent low temperature viscosity for easy cold starting during extreme cold weather.

| Properties | Method | Unit | Typical |
|---|---------------|--------------------|-----------|
| Viscosity Grade | | | SAE 0W-30 |
| Density, 15 °C | D 4052 | kg/m ³ | 851 |
| Kinematic Viscosity, 100 °C | D 445 | mm ² /s | 9.9 |
| Kinematic Viscosity, 40 °C | D 445 | mm ² /s | 53.5 |
| Viscosity Index | D 2270 | - | 177 |
| Apparent Viscosity, -35 °C | D 5293 | mPa.s | 5800 |
| Pour Point | D 97 | °C | -48 |
| Flash Point, COC | D 92 | °C | 205 |
| Viscosity at high temp. & high shear rate | CEC-L-36-A-90 | mPa.s | >-2.9 |

The figures above are not a specification. They are typical figures obtained within production tolerances.

