

# Q8 Formula Select C2 5W-30

## Description

Ultra high Performance Low SAPS SAE 5W-30 Synthetic Engine Oil for Toyota and Peugeot Citroën Euro 4 & Euro 5 engines equipped with or without DPF

## Application

- Engine oil for passenger cars and commercial vehicles with normally aspirated or turbo-charged gasoline, LPG or diesel Euro 4 & Euro 5 engines requiring Low SAPS engine oil.
- Specially developed for Toyota and Peugeot Citroën Euro 4 & Euro 5 engines.
- Backward compatible with Peugeot Citroën engines requiring ACEA A1/B1 and ACEA A5/B5 engine oil specification.

## Specifications

ACEA C2-04

## Benefits

- Reduces fuel consumption.
- LowSAPS formulation protecting Exhaust Catalyst and Diesel Particulate Filter.
- Excellent engine cleanliness and wear protection increasing engine durability.

Properties	Method	Unit	Typical
Viscosity Grade			SAE 5W-30
Density, 15 °C	D 4052	kg/m <sup>3</sup>	854
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	9.8
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	56.5
Viscosity Index	D 2270	-	162
Apparent Viscosity, -30 °C	D 5293	mPa.s	5300
Pour Point	D 97	°C	-33
Flash Point, COC	D 92	°C	205
Viscosity at high temp. & high shear rate	CEC-L-36-A-90	mPa.s	>-2.9

*The figures above are not a specification. They are typical figures obtained within production tolerances.*

