

Q8 Formula Special G Long Life 5W-30

Description

Ultra High Performance Low SAPS SAE 5W-30 Synthetic Engine Oil for Euro 5 & 6 engines for normal and extended drain intervals.

Application

- Engine oil for passenger cars and commercial vehicles with normally aspirated or turbo-charged gasoline, LPG or diesel Euro 5 & 6 engines requiring LowSAPS engine oil.
- Specially developed for GM Opel Euro 5 & 6 engines requiring GM Dexos2 engine oil specification.
- Backward compatible with GM Opel engines requiring GM-LL-A-025 & GM-LL-B-025 engine oil specifications.

Specifications

- GM Dexos2
- ACEA C3
- API SN/CF
- VW 502.00/505.01
- MB Approval 229.51 / 229.52
- BMW Longlife-04
- ACEA C2 suitable for use

Benefits

- Lubricant designed for GM Opel passenger car gasoline and diesel engines for Euro 5 & 6 models.
- LowSAPS formulation protecting Exhaust Catalyst and Diesel Particulate Filter.
- Excellent engine cleanliness and wear protection increasing engine durability.
- Reduces fuel consumption.
- Extended drain interval capability.

Properties	Method	Unit	Typical
Viscosity Grade			SAE 5W-30
Absolute Density, 15 °C	D 4052	kg/m ³	852
Kinematic Viscosity, 100 °C	D 445	mm ² /s	11.3
Kinematic Viscosity, 40 °C	D 445	mm ² /s	65.5
Viscosity Index	D 2270	-	167
Apparent Viscosity, -30 °C	D 5293	mPa.s	6200
Sulphated Ash	D 280	% mass	0.8
Pour Point	D 97	°C	-36
Flash Point	D 92	°C	210

The figures above are not a specification. They are typical figures obtained within production tolerances.

