

# Q8 Formula Techno FE Plus 5W-30

## Description

Synthetic Highly Fuel-efficient SAE 5W-30 Engine Oil meeting Ford WSS M2C 913-D for Euro 5 & 6 Ford engines giving a Fuel Economy Improvement up to 3% or more.

## Application

- For latest generation Ford Diesel and Gasoline engines meeting Euro 5 & Euro 6 emission legislation.
- Backwards compatible with all engines requiring Ford WSS M2C 912-A, 913-A/B & 913-C
- Specially developed for latest Ford engine technology using wet timing belts

## Specifications

ACEA A1/B1

ACEA A5/B5

Ford WSS M2C913-D

Ford WSS M2C913-C

Ford WSS M2C913-A/B

Meets the specification of Fiat 9.55535 G1

## Benefits

- Lubricant designed for latest generation Ford passenger car gasoline and diesel Euro 5 and 6 engines.
- Giving a Fuel Economy Improvement of up to 3% or more.
- Backwards compatible with Ford gasoline engines and diesel engines.
- Extended drain interval capability.
- High oil film strength under all engine operating conditions.
- Excellent engine performance at all driving conditions .
- Outstanding protection against foam formation, rust and corrosion .

Properties	Method	Unit	Typical
Viscosity Grade			SAE 5W-30
Absolute Density, 15 °C	D 4052	kg/m <sup>3</sup>	849
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	9.7
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	52.1
Viscosity Index	D 2270	-	171
Apparent Viscosity, -30 °C	D 5293	mPa.s	4600
Pour Point	D 97	°C	-36
Flash Point, COC	D 92	°C	215
Viscosity at high temp. & high shear rate	CEC-L-36-A-90	mPa.s	>=2.9

*The figures above are not a specification. They are typical figures obtained within production tolerances.*

